



ILS 6W



ILS 9W




ILS 13W & 18W

A competitive, interchangeable and architectural LED downlight system. An alternative light engine to an MR16 or GU10 lamp.

- A range of lumen outputs from 650lm to 2000lm
- Colour Temperatures: 2700k - 3000k - 4000k
- Beam Angles: 22°, 36° or 60° (/22D/36D/60D)
- Colours: Polished Aluminium finish as standard
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- IP Rating: IP20 as standard, other IP ratings available depending on bezel choice
- CRI90 as standard (/930/940)
- Housing: Aluminium
- Bezel: Polycarbonate reflector with aluminium coating

Product	MID/ILS Recessed ILS Downlight				
LED	/6W		/9W		18W
System Power Luminaire lumens (4000K)	8W 800lm		10W 1150lm		20W 2200lm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/927 2700k		/930 3000k		/940 4000k
Colour	Polished Aluminium				
Beam Angle Options	/22D 22 Degree		/36D 36 Degree		/60D 60 Degree
Emergency	/RME3 Remote three hour maintained emergency		/RME3-ST Remote three hour maintained self test emergency		/RME3-PRO Remote three hour DALI addressable emergency
/RME3-WI Remote three hour Wireless addressable emergency					
To Specify: MID ILS 9W, 60 degree beam angle, 4000k, 1150lm LED downlight, with an ILS bezel attachment; F4 in white. Part code: MID/ILS/F4/9W/1150lm/STD/940/WH/60D					



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

Style
Range abbreviation
Wattage
Lumens
Size
Driver
Colour Temperature
Options
Emergency