



ILS/D2/6W



ILS/D2/9W



ILS/D2/13W & ILS/D2/18W


The adjustable ILS D2 square downlight is a competitive, interchangeable and architectural LED downlight system.

An alternative light engine to a MR16 or GU10 lamp, the downlight is rotatable through 355 degrees.

- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°, 36° or 60° (/22D/36D/60D)
- Tunable White (/TWH)
- Colours: White, Silver, Grey or Black
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Adjustable
- 355° Rotation
- Dimensions: (Diameter x Depth) see page 25
113 x 113 x 100mm, 125mm, 130mm
- Cut-out Dimension: (Diameter) Ø95mm
- Housing: Aluminium
- Bezel: Polycarbonate, Semi specular reflector with aluminium coating


Product	MID/ILS/D2 Recessed ILS D2 Downlight				
LED	/6W	/9W	/13W	/18W	
System Power Luminaire lumens (4000K)	8W 650lm	11W 950lm	15W 1400lm	21W 2000lm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k			/840 4000k	
Colour	/WH White	/SLV Silver	/GR Grey	/BK Black	
Beam Angle Options	/22D 22 Degree		/36D 36 Degree		/60D 60 Degree
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency		/RME3-WI Remote three hour Wireless addressable emergency
To Specify: MID ILS D2 9W, 60 degree beam angle, 4000k, 950lm LED downlight, with an ILS bezel attachment; D2 in white. Part code: MID/ILS/D2/9W/950lm/STD/840/WH/60D					

6W




ILS/D2
Dimensions

9W



13W/18W



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

Style	Range abbreviation	Wattage	Lumens	Size	Driver	Colour Temperature	Options	Emergency
-------	--------------------	---------	--------	------	--------	--------------------	---------	-----------