



ILS6/D3/WH



ILS9/D3/WH



ILS13/D3/WH - ILS18/D3/WH

The adjustable ILS D3 downlight is a competitive, interchangeable and architectural LED downlight system.

An alternative light engine to a MR16 or GU10 lamp.

- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22° / 36° / 60°
- Colours: White, Silver, Grey or Black
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Adjustable
- 355° Rotation
- Bezel Dimension Ø90mm
- Cut-out Dimension Ø75mm
- Semi specular reflector
- Depth: See images below or page 23
- Materials: Aluminium Housing, Polycarbonate reflector with aluminium coating

Product	MID/ILS/D3 Recessed ILS D3 Downlight			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/6W 650lm	/9W 905lm	/13W 1100lm	/18W 1800lm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White	/SLV Silver	/GR Grey	/BK Black
Beam Angle Options	/22D 22 Degree	/36D 36 Degree		/60D 60 Degree
Emergency	/RME3 Remote Three hour maintained emergency	/RME3-ST Remote Three hour maintained self test emergency	/RME3-PRO Remote Three hour DALI addressable emergency	/RME3-WI Remote Three hour wireless addressable emergency
To Specify: MID ILS D3 9W, 60 degree beam angle, 4000k, 905lm LED downlight, with an ILS bezel attachment; D3 in white. Part code: MID/ILS/D3/9W/905lm/60D/STD/840/WH				

