

ILS G2 MATRIX



ILS/G2/9W/WH

The adjustable ILS G2 MATRIX downlight is a competitive, interchangeable and architectural LED adjustable downlight system. An alternative light engine to an MR16 or GU10 lamp.

- A range of lumen outputs from 650-1800lm
- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°, 36° or 60° (/22D/36D/60D)
- Colours: White, Grey or Black
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Adjustable
- Dimension: (Length x Width x Depth)
110 x 193 x 97mm(6W), 115mm(9W), 119mm(13 & 18W)
- Cut-out Dimension: (Length x Width)
100x180mm
- Housing: Aluminium
- Bezel: Polycarbonate reflector with aluminium coating
- CRI > 90 Available

Product	MID/ILS/G2/MATRIX Recessed ILS G2 Downlight										
LED	/6W		/9W		/13W		/18W				
System Power Luminaire lumens (4000K)	8W 723lm		11W 1219lm		15W 1494lm		21W 2049lm				
Driver	/STD Non Dimming		/DALI DALI Dimming		/SDIM Switch Dimming		/MDIM Mains Dimming		/WI Wireless Control		
Colour Temperature	/830 3000k					/840 4000k					
Colour	/WH White			/GR Grey			/BK Black				
Beam Angle Options	/22D 22 Degree			/36D 36 Degree			/60D 60 Degree				
Emergency	/RME3 Remote three hour maintained emergency			/RME3-ST Remote three hour maintained self test emergency			/RME3-PRO Remote three hour DALI addressable emergency			/RME3-WI Remote three hour Wireless addressable emergency	
To Specify: MID ILS G2 MATRIX 9W, 60 degree beam angle, 4000k, 1219lm LED downlight, with an ILS bezel attachment; G2 in white. Part code: MID/ILS/G2/MATRIX/9W/1219lm/STD/840/WH/60D											

Surface Mounting
Option (/SM)



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3	Style	Range abbreviation	Wattage	Lumens	Size	Driver	Colour Temperature	Options	Emergency
How to Specify									