



ILS9/G2/WH

- The adjustable ILS G2 MATRIX downlight is a competitive, interchangeable and architectural LED adjustable downlight system.
An alternative light engine to a MR16 or GU10 lamp.

- Colour Temperatures: 3000k - 4000k

- Beam Angles: 22°/ 36°/ 60°

- White and Black as standard, Grey also available

- Available with Dimming (/STD/DALI/SDIM/MDIM)

- Available with Emergency (/RME3/RME3-ST/RME3-PRO)

- Materials:

Aluminium Housing

Polycarbonate reflector with aluminium coating

- Adjustable

- Bezel Dimension 110x193mm

- Cut-out Dimension 100x180mm

Product	MID/ILS/G2/MATRIX Recessed ILS G2 Downlight			
Lamp	LED			
Lamp Power <small>Luminaire lumens (4000K)</small>	/6W 650lm	/9W 950lm	/13W 1400lm	/18W 2000lm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White	/BK Black		/GR Grey
Beam Angle Options	/22D 22 Degree	/36D 36 Degree		/60D 60 Degree
Emergency	/RME3 Remote Three hour maintained emergency	/RME3-ST Remote Three hour maintained self test emergency		/RME3-PRO Remote Three hour DALI addressable emergency
To Specify: MID ILS G2 MATRIX 9W, 60 degree beam angle, 4000k, 950lm LED downlight, with an ILS bezel attachment; G2 in white. Part code: MID/ILS/MATRIX/9W/950lm/60D/STD/840/WH/G2				

