



ILS/6W/PI-C/WH

- The adjustable plaster-in ILS downlight is a competitive, interchangeable and architectural LED downlight system.

An alternative light engine to a MR16 or GU10 lamp.

The ILS PI can be used with the ILS 6W and 9W engine wattages.

- Colour Temperatures: 3000k - 4000k
 - Beam Angles: 22°/ 36°/ 60°
- White as standard, Black and Grey also available
 - Available with Dimming (/STD/DALI/SDIM)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
 - Materials:
 - Aluminium Housing
 - Polycarbonate reflector with aluminium coating
- Adjustable
- 355° Rotation
- Bezel Dimension Ø70mm-Visible
 - Cut-out Dimension Ø70mm
- Depth: ILS 6W: 80mm ILS 9W: 100mm
 - Square version also available

Product	MID/ILS/PI-C Recessed ILS Plaster-in Downlight		
Lamp	LED		
Lamp Power <small>Luminaire lumens (4000K)</small>	/6W 650lm	/9W 950lm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Colour Temperature	/830 3000k		/840 4000k
Colour	/WH White	/SLV Silver	/GR Grey
Beam Angle Options	/22D 22 Degree	/36D 36 Degree	/60D 60 Degree
Emergency	/RME3 Remote Three hour maintained emergency	/RME3-ST Remote Three hour maintained self test emergency	/RME3-PRO Remote Three hour DALI addressable emergency
To Specify: MID ILS PI-C 9W, 60 degree beam angle, 4000k, 950lm LED downlight, with an ILS bezel attachment; PI in white. Part code: MID/ILS/9W/950lm/60D/STD/840/WH/PI-C			

