



ILS/S5/6W

ILS/S5/9W

The fixed ILS S5 downlight is a competitive, interchangeable and architectural LED downlight system. An alternative light engine to an MR16 or GU10 lamp.

- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°, 36° or 60° (/22D/36D/60D)
- Colours: White, Silver, Grey or Black
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- CRI > 90 Available (/930/940)
- Fixed
- IP Rating: IP20 as standard IP65 insert available
- Dimensions: (Length x Width x Depth) see page 25
80 x 80 x 60mm, 85mm
- Cut-out Dimension: (Diameter) Ø70mm
- Housing: Aluminium
- Bezel: Polycarbonate reflector with aluminium coating

Product	MID/ILS/S5 Recessed ILS S5 Downlight				
LED	/6W			/9W	
System Power Luminaire lumens (4000K)	8W 723lm			11W 1219lm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k			/840 4000k	
Colour	/WH White	/SLV Silver	/GR Grey	/BK Black	
Beam Angle Options	/22D 22 Degree		/36D 36 Degree		/60D 60 Degree
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency		/RME3-WI Remote three hour Wireless addressable emergency
To Specify: MID ILS S5 9W, 60 degree beam angle, 4000k, 1219lm LED downlight, with an ILS bezel attachment; S5 in white. Part code: MID/ILS/S5/9W/1219lm/STD/840/WH/60D					

