



ILS/SC/BK/SM

The ILS surface and suspended can is a competitive, interchangeable and architectural LED system. An alternative light engine to an MR16 or GU10 lamp.

- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°, 36° or 60° (/22D/36D/60D)
- Colours: White, Black or can have specified RAL colours
- Suitable for BESA fixing
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Mounting: Surface mounted as standard, Wire Suspension or Wire Suspension with ceiling rose (/SM/WS-ROSE/WS)
- Dimensions: (Diameter x Height) Ø135 x 207mm
- Housing: Aluminium
- Bezel: Polycarbonate reflector with aluminium coating
- CRI > 90 Available (/930/940)

Product	MID/ILS/SC Surface Mounted ILS SC Downlight						
LED	/6W		/9W		/13W	/18W	
System Power <small>Luminaire lumens (4000K)</small>	8W 723lm		11W 1219lm		15W 1494lm	21W 2049lm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control		
Colour Temperature	/830 3000k			/840 4000k			
Colour	/WH White		/SLV Silver		/GR Grey	/BK Black	
Beam Angle Options	/22D 22 Degree		/36D 36 Degree		/60D 60 Degree		
Emergency	/ME3 three hour maintained emergency		/ME3-ST three hour maintained self test emergency		/ME3-PRO three hour DALI addressable emergency		/ME3-WI three hour wireless addressable emergency
To Specify: MID ILS SC 9W, 60 degree beam angle, 4000k, 1219lm LED downlight, with an ILS attachment; SC, surface mounted in black. Part code: MID/ILS/SC/9W/1219lm/STD/840/BK/60D/SM							

