



ILS/SC/BK/SM

**- The ILS surface and suspended can is a competitive, interchangeable and architectural LED system.**

- Colour Temperatures: 3000k - 4000k
- Beam Angles: 22°/ 36°/ 60° (/22D/36D/60D)
- White (/WH) as standard, Black (/BK) and to specified RAL colours (/RAL)
- Suitable for BESA fixing
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Dimensions Ø135x207mm
- Materials: Aluminium Housing  
Polycarbonate reflector with aluminium coating
- Surface (/SM)
- Wire Suspension (/WS)
- Wire Suspension with ceiling rose(/WS-ROSE)

Product	MID/ILS/SC ILS Surface and Suspended Can			
Lamp Power	/6W	/9W	/13W	/18W
System Power <small>Luminaire lumens (4000K)</small>	8W 650lm	11W 950lm	15W 1400lm	21W 2000lm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White	/BK Black	/RAL Specified RAL Colour	
Beam Angle Options	/22D 22 Degree	/36D 36 Degree		/60D 60 Degree
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emer- gency		/ME3-PRO Three hour DALI addressable emer- gency
To Specify: MID ILS SC 9W, 60 degree beam angle, 4000k, 950lm LED downlight, with an ILS attachment; SC, surface mounted in black. Part code: MID/ILS/9W/950lm/60D/STD/840/SC/BK/SM				

