



**Low maintenance, affordable and efficient IP65 alternative to the MIS800.**

- A lumen output of 2633lm
- Colour Temperatures: 3000k - 4000k
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Mountings: Wall/Surface Mounting as standard
- Diffuser: Opal (/OP)
- Sensors: Available with microwave sensor for presence detection or corridor function (/MW/CDR)
- Suitable for BESA fixing
- IP Rating: IP65 as standard
- Dimensions: (Diameter x Depth) Ø430 x 135mm

|  |  |  |   |  |
|--|--|--|---|--|
| Product  | MIS/JUP<br>Surface LED circular              |  |   |  |
| Light Source   | LED  |  |   |  |
| System Power<br><small>Luminaire lumens (4000K)</small>  | /30.1W<br>2633lm                             |  |   |  |
| Size<br>Depth  | Ø430mm<br>135mm                              |  |   |  |
| Driver   | /STD<br>Non Dimming                          | /DALI<br>DALI Dimming  | /SDIM<br>Switch Dimming                                 | /WI<br>Wireless Control                                    |
| Colour<br>Temperature  | /830<br>3000k                                |  | /840<br>4000k   |  |
| Colour   | /WH<br>White                                 |  |   |  |
| Diffuser Options   | /OP<br>Opal Diffuser                         |  |   |  |
| Emergency  | /ME3<br>Three hour main-<br>tained emergency | /ME3-ST<br>Three hour main-<br>tained self test<br>emergency | /ME3-PRO<br>Three hour DALI<br>addressable<br>emergency | /ME3-WI<br>Three hour Wireless<br>addressable<br>emergency |
| To Specify: MIS JUPITER LED, 30.1W, 4000k, 2633lm LED surface circular finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS/JUP/30.1W/2633lm/DALI/840/WH/OP |  |  |   |  |

