



**The LEXCOB-FLEX is a flexible LED Tape that has chips on the board, this ensures a seamless design and provides an even light distribution. It's ideal for any professional environment.**

- A lumen outputs of 520lm or 1050lm
- Colour Temperatures: 2700K, 3000K, 4000K or 6500K
- Beam Angle: 180°
- Available in Standard or DALI Dimming (/STD/DALI)
- Wireless Control (/WI)
- Aluminium extrusion profiles and opal/clear diffuser options available, see page 76
- See LEXLED range for extrusions
- IP Rating: IP43 as standard, IP65-IP68 Available
- Flexible Strip
- CRI90 as standard
- Dimensions: (Length x Width x Height) See below
  - /5W - 5000mm (Max Length) x 4mm x 2mm
  - /10W - 5000mm (Max Length) x 4mm x 2mm
- Cut Lengths are in 50mm increments for 24v

Product	LEXCOB-FLEX COB-FLEX Tape			
Light Source	LED COB			
System Power Luminaire lumens (4000K)	/5W 520lm/M		/10W 1050lm/M	
Driver	/STD Non Dimming	/DALI DALI Dimming		/WI Wireless Control
Colour Temperature	/927 2700k	/930 3000k	/940 4000k	/965 6500k
Mounting	Recessed or surface mountings are available, depending on the choice of aluminium extrusion.			
Emergency	n/a			
To Specify: LEXCOB-FLEX, 4000k, 1 meter, 5W, 520lm LED downlight, CRI90 LED Tape with LED DALI dimming. Part code: MI/LEXCOB-FLEX/5W-m/520lm-m/DALI/940/1M				

COB-FLEX Tape  
Dimensions

