

MAG-48V TRK-5STAR



The MAG-48V TRK-5STAR is made from an aluminium body for optimal heat dissipation, with built-in magnets for secure mounting, and an adjustable design for versatile lighting angles. It supports DALI, 0-10V, and Zigbee control systems.

- A range of lumen outputs of 482lm
- Colour Temperatures: 2700k - 6000k & Tuneable white
- Beam Angles: 15°, 30° or 45° (/15D/30D/45D)
- Colours: Black or White (/BK/WH)
- Available with Dimming (/STD/0-10V/DALI)
- Wireless dimming available (/WI)
- Mountings: 48v Track Mounted
- CRI80 as standard, CRI90 available
- Dimensions: (Length x Width x Height)
138 x 59 x 35mm

| | | | | | | | | | | | | |
|---|---|--|-------------------------|--|-----------------------|--|--------------------------|--|--------------------|--|---------------|--|
| Product | MAG-48V TRK-5STAR LED Linear Lamp Suited For 48V Mag-Track | | | | | | | | | | | |
| Light Source | LED | | | | | | | | | | | |
| System Power Luminaire lumens (4000k & 45°) | /5W 482lm | | | | | | | | | | | |
| Size | 138 x 59 x 35mm (Length x Width x Height) | | | | | | | | | | | |
| Driver | /STD Non Dimming | | /0-10V 0-10V Dimming | | /DALI DALI Dimming | | /WI Wireless Controls | | | | | |
| Colour Temperature | /827 2700k | | /830 3000k | | /840 4000k | | /850 5000k | | /850 5000k | | /860 6000k | |
| Colour | /WH White | | | | | | /BK Black | | | | | |
| Beam Angle | /15D 15 Degrees | | | | /30D 30 Degrees | | | | /45D 45 Degrees | | | |
| Emergency | Remote EMLED MAG TRK available | | | | | | | | | | | |
| To Specify MI/MAG-48V TRK-5STAR, 5W, 4000k, 482lm, 45 degree beam angle, CRI 80, LED linear track spotlight and supplied with DALI control gear and finished in black. Part code: MI/MAG-48V/TRK-5STAR/5W/847lm/DALI/940/45D/BK | | | | | | | | | | | | |

Side Profile Dimensions

