


MAG-48V TRK-LINDA




The MAG-48V TRK-LINDA lamp is a track-type quick-swap light that uses a magnet as well as having three installation modes. With its minimal design ideally suited for showrooms, office, store and etc.

- A lumen output of 840-3300lm
- Colour Temperatures: 3000K - 4000K - 5000K - 6000K
- Beam Angles: (/110D)
- Colours: Black or White (/BK/WH)
- Available with Dimming (/STD/0-10V/DALI)
- Wireless dimming available (/WI)
- Refer to track system **page 84** for the following mounting, Surface, Recessed and Wire suspended
- CRI90 as standard
- Dimensions: (Length x Width x Height)
 - /7W - 294 x 22 x 43mm
 - /15W - 574 x 22 x 43mm
 - /22W - 854 x 22 x 43mm
 - /30W - 1134 x 22 x 43mm


Product	MI/MAG-48V TRK-LINDA lamp LED Linear Lamp			
Light Source	LED			
System Power Luminaire lumens (4000k)	/7W 840lm	/15W 1800lm	/22W 2640lm	/30W 3300lm
Size (Length)	/3 294mm	/6 574mm	/9 854mm	/12 1134mm
Driver	/STD Non Dimming	/0-10V 0-10V Dimming	/DALI DALI Dimming	/WI Wireless Controls
Colour Temperature	/930 3000k	/940 4000k	/950 5000k	/960 6000k
Colour	/WH White		/BK Black	
Beam Angle	/110D 110 Degrees			
Emergency	n/a			
To Specify: MAG-48V TRK-LINDA, 15W, 4000k, 995lm, 110 degree beam angle, CRI 90, LED track spotlight Surface Mounted and supplied with DALI control gear and finished in black. Part code: MI/MAG-48V/TRK-LINDAA/15W/6/995lm/DALI/940/100D/SM/BK				



Side Profile of 30W
Dimensions



MAG-48V TRK



The MAG-48V TRK is a 48V low-voltage magnetic track system with a sleek aluminum profile designed for modern lighting applications. it can be use with a arange of MAG-48V luminaires for a customisable setup.

- Colours: Matt White or Matt Black (/WH/BK)
- The optimal rail connections is no more than 40 meters
- Connectors: See previous page for more details (/VIL/VEL/LL/TM/CS/HL) * If required*
- Compatible with any brand external 48V output constant voltage switching power supply
- Magnetic End Caps (/MC)
- Mountings: Plaster-in, Surface mounted, Wire Suspended or Rod Suspended (/P/SM/WS/RS)
- IP Rating: IP20
- Section View Dimensions: See image below
- Dimensions: Standard Magnetic Track Length - 0.5M, 1.0M, 1.5M or 2.0M
- Please contact technical department for more information

