


**A slimline linear wall mounted luminaire ideal for corridors and other circulation areas.**

- A range of lumen outputs 1092-2698lm
- Colour Temperatures: 4000k
- Colours: White or Silver, other colours available (/WH/SLV)
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Distribution: Direct or Direct/Indirect options (/DL/UDL)
- Mounting: Wall mounted as standard
- Dimensions: (Length x Width x Height)
  - /450 - 450 x 150 x 50mm
  - /600 - 600 x 150 x 50mm
  - /900 - 900 x 150 x 50mm
  - /1200 - 1200 x 150 x 50mm

Product	MIS/MARCH Wall mounted LED Luminaire			
Light Source	LED			
System Power Luminaire lumens (4000K)	/10W 1092lm	/14W 1484lm	/20W 2214lm	/26W 2698lm
Size	/450 450mm	/600 600mm	/900 900mm	/1200 1200mm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/840 4000k			
Colour	/WH White		/SLV Silver	
Diffuser Options	/OP Opal			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emer- gency
To Specify: MARCH LED, 20W, 2214lm, 4000k, LED wall mounted finished white with opal diffuser and supplied complete with standard control gear. Part code: MIS/MARCH/20W/2214lm/900/STD/840/WH/OP				



Emergency Options Colour Temperature Driver Size Lumens Wattage Range abbreviation Style How to Specify

MIS/RANGE/SLV/M/840/OP/ME3