



- A slimline linear wall mounted luminaire ideal for corridors and other circulation areas.

- Available in a range of lumen outputs 1092lm-2698lm
  - Colour Temperatures: 4000k
  - Up/downlight as standard
  - Wall mounted as standard
- Available in White or Silver (/WH/SLV), other colours available
  - Available with Dimming (/STD/DALI/SDIM)
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
  - Dimensions: 450/600/900/1200 x 150 x 50mm

Product	MIS/MARCH Wall mounted LED Luminaire			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/10W 1092lm	/14W 1484lm	/20W 2214lm	/26W 2698lm
Size	/4 450mm	/6 600mm	/9 900mm	/12 1200mm
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/840 4000k			
Colour	/WH White		/SLV Silver	
Diffuser Options	/OP Opal			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: MARCH LED, 20W, 2214lm, 4000k, LED wall mounted finished white with opal diffuser and supplied complete with standard control gear. Part code: MIS/MARCH/LED/20W/2214lm/900/STD/840/WH/OP				

