




The MI-STAND is a bollard with downward-facing front illumination, featuring an anti-dazzle louvre for effective walkway and path lighting. Made from Low copper content die-cast aluminium and finished with epoxy-based primer.

- A lumen output of 800lm
 - Colour Temperature: 2700k - 3000k - 4000k
 - Colour: Dark Grey, Light Grey or Bronze (/DGR/LGR/BR)
 - Available with dimming (/STD/MDIM)
 - Emergency: Please speak with technical
 - Mounting: Root Mounted
- IP Rating: IP65
 - Head Cap Options: Hooded Shield
 - Housing: Low copper content die-cast aluminium
 - Dimensions: (Length x Width x Depth)
495 x 86 x 73mm

Product	MI-STAND Bollard I IP65 LED Luminaire		
Light Source	LED		
System Power Luminaire lumens (4000K)	/8W 800lm		
Size	495 x 86 x 73mm		
Driver	/STD Non Dimming		/MDIM Mains Dimming
Colour Temperature	/827 2700k	/830 3000k	/840 4000k
Colour	/DGR Dark Grey	/LGR Light Grey	/BR Bronze
Emergency	Please contact technical for more info		
To Specify: MI-STAND LED, 8W, 800lm, 4000k, LED bollard anchor root mounted luminaire finished dark grey supplied with standard integral control gear. Part code: MI-STAND/8W/800lm/STD/840/DGR			

Dark Grey Version



Exterior