



- A high quality LED surface mounted LED downlight, also available as a pendant. Designed for direct mounting onto solid ceiling systems, or where the ceiling void is too shallow to accept a recessed downlight.

- Available in a range of lumen outputs from 957lm-2910lm
- Colour Temperatures: 3000k - 4000k - Tunable White (/TWH)
 - Available with Dimming (/STD/DALI/SDIM/MDIM)
- Bezel Options: White/ Chrome/ Brushed Aluminium (/WH/CH/BA)
 - Pendant Version (/WS)
- Reflector Options: Faceted Reflector/ Satin Etched/ Highly Specular (/FR/SE/HS)
 - Dimensions: Ø200mm x 152mm depth

Product	MID130/SURF Surface MID130 Downlight			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/9.5W 957lm	/17.5W 1740lm	/26.5W 2610lm	
Size	Ø200mm x 152mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k	/840 4000k		/TWH Tunable White
Bezel Colour	/WH White	/CH Chrome	/BA Brushed Aluminium	
Reflector Options	/FR Faceted Reflector	/SE Satin Etched	/HS Highly Specular	
Emergency	Not available as emergency			
To Specify: MID130 SURF LED, 17.5W, 4000k, 1740lm LED downlight finished white supplied with faceted reflector and standard control gear. Part code: MID130/SURF/LED/17.5W/1740lm/STD/840/FR				

