



MID200 Satin Etched



IP54 cover (/IP54)



Dropped Clear Glass (/DGCL)



Dropped Fully Etched Glass (/DGFE)



Dropped Etched Halo Glass (/DGEH)



IP65 cover (/IP65)

A high quality LED downlight providing flexibility through interchangeable decorative and IP rated attachments.

- A range of lumen outputs 1124 -3014lm
- Colour Temperatures: 3000k - 4000k - Tunable White
- Colours: White RAL9010 & RAL9016, Black or Grey
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Reflectors: Satin Etched, Specular or Faceted (/SE/SR/FR)
- IP Rating: IP20 as standard, IP54 and IP65 available
- Dimensions: (Diameter x Depth)
Ø195 x 115mm
- Cut-out Dimensions: (Diameter)
Ø176mm

Product	MID200/LED Recessed MID200 Downlight			
Light Source	LED			
System Power <small>Luminaire Lumens (4000K)</small>	/9.9W 1124lm	(/TW) -/17.7W 1860lm	/18.2W 1986lm	/26.4W 3014lm
Size Cut-out	Ø195mm Ø176mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k	/TWH Tunable White
Bezel Colour	/WH-RAL9010 White-RAL9010	/WH-RAL9016 Brilliant White	/BK Black-RAL9005	/GR Grey-RAL9006
Reflector Options	/SE Satin Etched		/SF Specular Reflector	/FR Faceted Reflector
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: MID200 LED, 9.9W, 4000k, 1124lm LED downlight finished white supplied with satin etched reflector, DALI and Wireless control gear. Part code: MID200/9.9W/1124lm/WI/DALI/840/WH/SE				

More Reflector Options



40° Specular reflector (/SF)



50° Multifaceted reflector (/FR)

