



- Colour Temperature: 4500k
- Colour: White (/WH)
- Emergency Options:
Three Hour Maintained (/ME3),
Three Hour Non Maintained (/NME3),
Self Test (/ME3-ST),
DALI Addressable Emergency (/ME3-PRO)
- Double sided legend panel as standard (/DS)
- If ME3-WI is required please speak to Technical
- Mounting: Surface mounted
- Viewing distance: 25 meters
- IP Rating: IP65
- Supplied with EN7010 format legends as standard
BS5499 format legends available upon request.
- Dimensions: (Length x Width x Depth)
350 x 120 x 65mm (without sign exit sign)

Product	MIEX-CM Version 2 A Ceiling Mounted Emergency Sign			
Light Source	LED			
System Power	/3W 150lm (without sign exit sign)			
Size	350 x 120 x 200mm (without sign exit sign)			
Driver	/STD Non Dimming			
Colour Temperature	4500k			
Colour	/WH White			
Emergency	/NME3 Three hour non maintained emergency	/NME3 Three hour non-maintained emergency	/NME3-ST Three hour non maintained self test emergency	/NME3-PRO Three hour non DALI addressable emergency
To Specify: MIEX-CM V2 LED, 3W, 4500k as standard, LED surface mounted finished white supplied complete with standard control gear, arrow down legend and three hour non-maintained emergency. Part code: MIEX-CM/V2/LED/3W/WH/NME3/AD				

(AU) - Arrow Up



(AR) - Arrow Right

(AL) - Arrow Left

(AU) - Arrow Down

MIR/RANGE/5W/LM/SIZE/DIM/840/OPT/ME3

How to Specify

range: abbreviation	style
---------------------	-------

Banque abbreviation

Lumens

Size

Driver

Colour Temperature

Options

Emergency