





## A IP65 double sided LED emergency sign with a polycarbonate housing with opal diffuser

- -3W LED
- Colour Temperature: 6500k
- Colour: White (/WH)
- Emergency Options: Three Hour Maintained (/ME3), Three Hour Non Maintained (/NME3), Self Test (/ME3-ST), DALI Addressable Emergency (/ME3-PRO)
- Double sided legend panel as standard (/DS)
- If ME3-WI required please speak to Technical

- Mounting: Surface mounted, Wire suspended or Semi Recessing Trim (/SM/WS/SRT)
- -Viewing distance: 28 meters
- **-** Supplied with EN7010 format legends as standard. BS5499 Format legends available upon request
- IP Rating: IP65
- Dimensions: (Length x Width x Depth) 350 x 108 x 204mm
- Cut-out Dimensions: (Length x Width) 330 x 90mm

Product	MIEX-CM A Ceiling Mounted Emergency Sign			
Light Source	LED			
System Power	/3W			
Size	350 x 108 x 204mm			
Driver	/STD Non Dimming			
Colour Temperature	6500k			
Colour	/WH White			
Emergency	/ME3 Three hour main- tained emergency	/NME3 Three hour non-maintained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency

To Specify: MIEX-CM LED, 3W, 6500k as standard, LED surface mounted finished white supplied complete with standard control gear, arrow down legend and three hour maintained emergency.

Part code: MIEX-CM/LED/3W/WH/ME3/AD

(AU) Arrow Up (AD) Arrow Do (AR) Arrow Right How to Specify

**Legend Options**