


MIR550 LED



- An attractive direct/indirect LED luminaire incorporating a highly efficient diffuser for increased performance. Designed to give an ambience to office lighting and commercial applications using a perforated basket.

- A lumen output of 3142lm
- 5 year system warranty
- Colour Temperatures: 3000k - 4000k - 5000k - Tunable White (TWH)
 - Available with Dimming (/STD/DALI/SDIM/MDIM)
 - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Exposed Tee ceilings, Spring Tee and other ceiling options available
 - Diffuser Options: Polar White / Microprism / Lumieo Panel (/PW/ MPO/MPOLP)
- Additional lumen and wattage options available. Please contact technical for details.
- Dimensions: 600 x 600 x 95mm
- Refer to page 89 for ceiling system options

Product	MIR550 Recessed LED Modular			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/35W 3142lm			
Size Cut-Out	/66 600 x 600mm 594 x 594mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/830 3000k	/840 4000k	/850 5000k	/TWH Tunable White
Colour	/WH White			
Diffuser Options	/PW Polar White	/MPO Micro Prismatic Optic		/MPOLP MPO with Lumieo
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: MIR550 LED, 35W, 4000k, 3142m LED modular recessed finished white supplied complete with DALI control gear and polar white diffuser. Part code: MIR550/LED/66/35W/3142lm/66/DALI/840/WH/PW				

