



- An IP65 rated (front) LED luminaire. Ideal for use in environments such as laboratories, hospitals, bathrooms, kitchens, and clean-room environments. Designed to integrate with specific ceiling systems as well as standard lay-in and concealed grid ceilings.

- Range of lumen outputs 4004lm-8008lm
- Dimensions: 600 x 600 x 91mm, 1200 x 300 x 91mm, 1500 x 300 x 91mm, 1200 x 600 x 91mm
- Colour Temperatures: 3000k - 4000k -5000k - Tunable White (TWH)
- Wire suspended or surface mounted options available
- Exposed Tee ceilings, Spring Tee and other ceiling options available
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Additional lumen and wattage options available. Please contact our technical department for details.
- Available in Emergency (/ME3/ME3-ST/ME3-PRO)
- Front and rear IP rated options available. IP65 front rating as standard, IP54 and IP65 rear available (/IP54R/IP65/IP65R)
- Diffuser Options: Polar White / Microprism / Lumieo Panel (/PW/MPO/MPOLP)
- 5 year system warranty
- Refer to page 89 for ceiling system options

Product	MIR700 Recessed LED IP65 Modular			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/33.2W 4004lm	/33.2W 4004lm	/41.6W 5005lm	/66.4W 8008lm
Size	/66 600 x 600mm	/123 1200 x 300mm	/153 1500 x 300mm	/126 1200 x 600mm
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/830 3000k	/840 4000k	/850 5000k	/TWH Tunable White
Bezel Colour	/WH White			
Diffuser Options	/PW Polar White	/MPO Micro Prismatic Optic		/MPOLP MPO with Lumieo
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: MIR700 LED, 33.2W, 4000k, 4004lm LED modular recessed finished white supplied complete with DALI control gear, polar white diffuser and IP65 rated. Part code: MIR700/LED/33.2W/4004lm/66/DALI/840/WH/PW/IP65				

