



The Cell range features 4-cell or 7-cell linear fittings, suitable for track, surface, or recessed mounting. Its compact, distinctive design offers versatility and a sleek, modern aesthetic.

- A range of lumen outputs from 897-1436m
 - Colour Temperatures: 3000k - 4000k
 - Beam Angles: 50° or 80° (/50D/D)
 - Colours: Black or White (/BK/WH)
 - Available with Dimming (/STD/DALI)
- Mountings: Surface Mounted or Wire Suspended (/SM/WS)
 - Recessed & Track Mounted versions available
 - CRI80 as standard, CRI90 available
 - Dimensions: (Length x Width x Height)
285 x 50 x 85mm

Product	MID/7CELL LED Linear Lamp Suited For Track			
Light Source	LED			
System Power Luminaire lumens (4000K)	/6W 897lm	/7.1W 1077m	/8.2W 1256m	/9.4W 1436lm
Size	285 x 50 x 85mm (Length x Width x Height)			
Driver	/STD Non Dimming		/DALI DALI Dimming	
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White RAL9016		/BK Black RAL9005	
Beam Angle	/50D 50 Degrees		/80D 50 Degrees	
Emergency	N/A			
To Specify: MID/7CELL 8.2W, 4000k, 1256lm, 50 degree beam angle, LED surface mounted linear spotlight supplied with DALI control gear and finished in black. Part code: MID/4CELL/8.3W/1256lm/DALI/840/BK/50D/SM				

Track Mounted Version
MI/TRK-7CELL



Recessed Version
MIR/7CELL

