



A surface mounted IP65 rated stand alone LED emergency fitting suitable for corridors. Quick and easy installation.

- A lumen output of 230lm or 280lm
- Colour Temperature: 6500k
- Lens: Corridor Lens or Open Area Lens available (/CL/OA)
- Colour: White or Black (/WH/BK)
- Emergency Options: Three Hour Non Maintained(/NME3), Self Test (/NME3-ST), DALI Addressable Emergency (/NME3-PRO)
- Mounting: Surface Mounted
- IP Rating: IP65
- Dimensions: (Length x Width x Depth) 155 x 155 x 46mm
- 4 Year battery life warranty

Product	MIS/EMLED-ECO/SQ IP65 Square Standalone Emergency Luminaire		
Light Source	LED		
Lens Options	/CL Corridor Lens	/OA Open Area Lens	
System Power	/1.6W 230lm (/CL) only	/1.6W 280lm (/OA) only	
Size	155 x 155 x 46mm		
Colour Temperature	6500k		
Colour	/WH White	/BK Black	
Emergency	/NME3 Three hour non-maintained emergency	/NME3-ST Three hour non-maintained self test emergency	/NME3-PRO Three hour non-maintained DALI addressable emergency
To Specify: MIS/EMLED-ECO 1.6W, 280lm, LED surface mounted, IP65 rated, finished white supplied complete with an open area optic and three hour non-maintained emergency. Part code: MIS/EMLED-ECO/SQ/1.6W/280lm/WH/OA/NME3			

