



## MIS/EMLED/C

## A ceiling mounted, LED stand alone emergency fitting. Quick and easy installation

- A lumen output of 266lm
- Colour Temperature: 6500k
- Lens: Open Area, Corridor or High Level (/OA/CL/HI-LEVEL)
- Colour: White RAL9016 or Black RAL9005 (/WH/BK)
- Emergency Options: Three Hour Non Maintained (/NME3),
  Self Test (/NME3-ST),

DALI Addressable Emergency (/NME3-PRO)

- Mounting: Surface Mounted
- Features Halo Effect Bi-Colour Charge LED
- Dimensions: (Diameter x Depth)

Ø155 x 58mm

- 4 Year battery life warranty

Product	EMLED Standalone Emergency Luminaire			
Light Source	LED			
System Power	/3W 266lm			
Installation	MIS/C/ Surface Circular			
Colour Temperature	6500k			
Colour	/WH White-RAL9016		/BK Black-RAL9005	
Lens Options	/OA Open Area	/CL Corridor Lens		/HI-LEVEL High Level
Emergency	/NME3 Three hour non-main- tained emergency	/NME3-ST Three hour non-maintained self test emergency		/NME3-PRO Three hour non-maintained DALI addressable emergency

To Specify: EMLED 3W, 250Im, LED surface mounted finished white supplied complete with an open area optic and three hour non-maintained emergency. Part code: MIS/EMLED/3W/266Im/WH/OA/NME3



