

# MIVP-ECO



**- A cost effective, reinforced opal polycarbonate vapour resistant luminaire supplied with stainless steel retention bracket for body, suitable for all indoor and external under cover applications only.**

- A range of lumen outputs from 1500-6490lm
  - 5 year system warranty for LED
  - Colour Temperatures: 4000k
- Available with Dimming (/STD/1-10V/DALI/SDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Screw fix mounted as standard. Stainless steel fixing clips are available (/SSSB)
- Rated IP65
- Unique frosted opal polycarbonate diffuser
- Dimensions: Length: 665/1275/1575 Width: 84/134 Depth: 98.5mm
- Available with wire suspension (/WS)
- Suitable for all indoor and external under cover applications only.

Product	MIVP-ECO Linear LED Vapour Proof Luminaire					
Lamp	LED					
Lamp Power Luminaire lumens (4000K)	/11.5W 1500lm	/20.9W 2590lm	/27.6W 3780lm	/39W 5190lm	/34.5W 4730lm	/48.9W 6490lm
Size	/6 665 x 134mm		/12 1275 x 84mm	/12 1275 x 134mm	/15 1575 x 84mm	/15 1575 x 134mm
Driver	/STD Non Dimming		/1-10V 1-10V Dimming		/DALI DALI Dimming	/SDIM Switch Dimming
Colour Temperature	/840 4000k					
Body Colour	Grey					
Diffuser Options	Opal Diffuser					
Emergency	/ME3 Three hour main- tained emergency		/ME3-ST Three hour maintained self test emergency			/ME3-PRO Three hour DALI addressable emergency
To Specify: MIVP-ECO LED LED, 27.6W, 3780lm, 1275mm, 84mm wide, 4000k, LED surface mounted finished grey supplied complete with standard control gear. Part code: MIVP-ECO/LED/27.6W/3780lm/12/STD/840						

