



The MIVP-HD is a heavy duty die cast aluminium housing and top frame with grey powder coat finish. Can be tapped for side conduit entry.

- A range of lumen output of 5,695-15,930lm
- Colour Temperature: 4000k
- Lens: Opal polycarbonate vandal-resistant
- Colour: Grey as standard (/GR)
- Standard Non Dimming (/STD)
- Mounting: Surface mount or optional quick-mount bracket, adjustable bracket or stainless steel yoke (/QMB/AB/SSY)
- IP Rating: IP66
- IK Rating: IK10
- Temperature Range -40C to +50C
- Die cast aluminium housing and top frame with grey powder coat finish.
- Dimensions: (Length x Width x Height) 614/1247 x 178 x 102mm

Product	MIVP-HD Surface IP66 LED Luminaire			
Light Source	LED			
System Power Luminaire lumens (4000K)	/58W 5695lm	/78W 8021lm	/126W 13172lm	/152W 15930lm
Size	614 x 178 x 102mm		1247 x 178 x 102mm	
Driver	/STD Non Dimming			
Colour Temperature	/840 4000k			
Colour	/GR Grey			
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	
To Specify: MIVP-HD LED, 152W, 15930lm, 4000k, LED surface mounted luminaire finished grey complete with standard integral control gear. Part code: MIVP-HD/152W/15930lm/STD/840/GR				



Exterior