





**- The MIVP-HD is a heavy duty die cast aluminium housing and top frame with gray powder coat finish.
Can be tapped for side conduit entry.**

- Providing a lumen output of 5695-15930lm
- Colour Temperature: 4000k
- Die cast aluminium housing and top frame with gray powdercoat finish.
 - Rated IP66 - IK Rating 10.
 - Temperature Range -40C to +50C
 - Opal polycarbonate vandal-resistant lens.
- Surface mount or use optional quick-mount bracket, adjustable bracket or stamped steel yoke (/QMB/AB/SSY)
- Dimensions: 614/1247 x 178 x 102mm (L x W x D)

Product	MIVP-HD Surface IP66 LED Luminaire			
Lamp	LED			
System Power <small>Luminaire Lumens (4000K)</small>	/58W 5695lm	/78W 8021lm	/126W 13172lm	/152W 15930lm
Size	614 x 178 x 102mm		1247 x 178 x 102mm	
Driver	/STD Non Dimming			
Colour Temperature	/840 4000k			
Colour	/GR Grey			
To Specify: MIVP-HD LED, 152W, 15930lm, 4000k, LED surface mounted luminaire finished grey supplied with complete with standard integral control gear. Part code: MIVP-HD/152W/15930lm/STD/840/GR				



Exterior