MOONDISC-IP65









-Low maintenance, affordable and efficient IP65 LED bulkhead luminaire. Designed with integral sensor options.

- LED boards providing a range of lumen outputs of 1000-1500lm

- Colour Temperature: 4000k

- Diffuser: Opal

- IP65 as standard

- Available with microwave sensor for presence detection and presence detector for corridor function available (/MW/CDR)

- Available with Emergency (/ME3/ME3-ST/ME3-PRO)

- Dimensions: Ø 340mm x 112mm

Product	MIS/MOONDISC-IP65 Surface LED circular			
Lamp	LED			
Lamp Power	,		/22W 800lm	
Size Depth	Ø340mm 112mm			
Driver	/STD Non Dimming			
Colour Temperature	/840 4000k			
Colour	/WH White			
Diffuser Options	/OP Opal Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintaine emergency	ed self test	/ME3-PRO Three hour DALI addressable emergency

MIR/RANGE/SW/LW/SIZE/DIM/840/0

MIR/RANGE/SW/LW/SIZE/DIM/840/0

MIR/RANGE/SW/LW/SIZE/DIM/840/0

MIR/RANGE/SW/LW/SIZE/DIM/840/0

MIR/RANGE/SW/LW/SIZE/DIM/840/0

MIR/RANGE/SW/LW/SIZE/DIM/840/0

MIR/RANGE/SW/LW/SIZE/DIM/840/0

To Specify: MIS MOONDISC-IP65 LED, 15W, 4000k, 1250lm LED surface circular finished white supplied complete with standard control gear and opal diffuser. Part code: MIS/MOONDISC-IP65/15W/1250lm/STD/840/WH/OP

