




The NOODLE is a high-performance surface or suspended cylindrical linear luminaire, delivering even, functional illumination for interior settings, with customizable lengths and joinable runs to suit a variety of applications.

- A range of lumen outputs from 2300-9200lm
- Colour Temperatures: 3000K - 4000K - 4500K - 5000K
- Colours: White (/WH)
- Available with Dimming (/STD/0-10V/DALI)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Mounting: Surface Mounted or Wire Suspended (/SM/WS)
- Diffuser: Opal
- Sensor: Bluetooth DC12V, high voltage Microwave and PIR (/DC12/MW/PIR)
- Distribution: Direct or Direct/Indirect options (/DL/UDL)
- Dimensions: Length x Width x Height)
 - /610mm - 610 x 86 x 82mm
 - /1198mm - 1198 x 86 x 82mm
 - /2388mm - 2388 x 86 x 82mm

Product	MIS/NOODLE Surface Mounted or Suspended LED Luminaire			
Light Source	LED			
System Power <small>Luminaire lumens (4000K)</small>	/20W 2300lm	/40W 4600lm	/80W 9200lm	
Lengths	/610mm 610 x 86 x 82mm	/1198mm 1198 x 86 x 82mm	/ 2388mm 2388 x 86 x 82mm	
Driver	/STD Non-Dimming		/DALI DALI Dimming	
Colour Temperature	/830 3000K	/840 4000K	/845 4500K	/850 5000k
Colour	/WH White			
Diffuser Options	/OP Opal			
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: NOODLE LED, 20W, 2300lm, 4000K, LED suspended with a Opal diffuser supplied complete with DALI control gear, and White exterior. Part code: MIS/NOODLE/20W/2300lm/DALI/840/WH/OP/WS/610mm				

Noodle Installation



Surface & Suspended