

PERISCOPE-C



6W



11W



15W

A small adjustable downlight suitable for commercial and residential premises. The Periscope can be used as a downlight or adjusted to rotate and angle, as shown in the above images.

- A range of lumen outputs from 350-1300lm
- Colour Temperatures: 3000k - 4000k.
- Beam Angle: 15° - 55° options available
- 350 Degree Rotation 90 Degree Tilt
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Bezel Options: Black or White (/BK/WH)
- Reflector Colours: White, Black, Gold (/WHR/BKR/GDR)
- CRI90 as standard
- Dimensions: (Diameter x Height)
 - /6W - Ø54 x 72mm
 - /11W - Ø88 x 150mm
 - /15W - Ø110 x 165mm

Product	MID/PERI-C Recessed Adjustable LED Downlight								
Light Source	LED								
System Power Luminaire lumens (4000K)	PERI-C/6W 350lm			PERI-C/11W 800lm			PERI-C/15W 1300lm		
Size Cut-out	Ø54 x 72mm Ø46mm			Ø88 x 150mm Ø80mm			Ø110 x 165mm Ø100mm		
Beam Angle	15°	30°	55°	18°	24°	36°	15°	25°	30°
Driver	/STD Non Dimming		/DALI DALI Dimming		/SDIM Switch Dimming		/MDIM Mains Dimming		/WI Wireless Control
Colour Temperature	/930 CRI > 3000k					/940 CRI > 4000k			
Bezel Colour	/WH White					/BK Black			
Decorative Ring	/WH White			/BK Black			/GD Gold		
Emergency	/ME3 Three hour maintained emergency		/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency		/ME3-WI Three hour wireless addressable emergency		
To Specify: PERISCOPE-C, 6W, 4000k, 350lm LED downlight finished white with 30° beam and black decorative reflector, supplied with DALI dimming control gear. Part code: MID/PERI-C/6W/350lm/DALI/940/WH/30D/BKR									

