



A suspended Direct/Indirect Phantom. The Phantom provides an elegant source of illumination through its unique transparent optic.

- A lumen output of 6340lm
- Colour Temperatures: 3000k - 4000k - 6000k
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Integral control gear for the standard product.
- Distribution: Direct/Indirect
- Mountings: 4-point wire suspension as standard.
- Supplied with a remote box suitable for surface mounting.
- Dimensions: (Length x Width x Height) 1195 x 295 x 22mm

Product	MIS/PHAN Suspended Direct / Luminaire			
Light Source	LED			
System Power Luminaire lumens (4000K)	/60W 6340lm			
Size	1195mm x 295mm x 22mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/830 3000k	/840 4000k	/860 6000k	
Colour	/WH White		/BK Black	
Diffuser Options	/CL Clear optic			
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency	/RME3-WI Remote three hour Wireless addressable emergency
To Specify: PHANTOM, 60W, 4000k, 6340lm LED suspended linear finished white supplied complete with standard control gear and clear diffuser. Part code: MIS/PHAN/60W/6340lm/STD/840/WH/CL				

