




The PYROX is an explosion-proof LED luminaire designed for extreme conditions, certified for hazardous areas zone classification 1 & 21.

- A range of lumen outputs from 1756- 8780lm
- Colour Temperatures: 4000k
- Colour: Grey (/GR)
- Available with Dimming (/STD/1-10V/DALI/SDIM) (/STD/DALI/1-10V)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Hazardous Area Classification: Zone 1 & 21
- Mountings: Wire Suspended as standard (/WS)
- Diffuser: Opal or Clear Diffuser available (/OP/CL)
- IP Rating: IP66
- IK Rating: IK10
- Dimensions: (Length x Depth, including clamp)
 - /7 - 748 x 208mm
 - /13 - 1357 x 208mm
 - /16 - 1659 x 208mm

Product	PYOX Industrial LED Luminaire					
Light Source	LED					
System Power Opal diffuser in 4000K	/12W 1756lm	/24W 3512lm	/24W 3512lm	/48W 7024lm	/30W 4390lm	/60W 8780lm
Length	/7 748mm		/13 1357mm		/16 1659mm	
Driver	/STD Non Dimming		/DALI DALI Dimming		/1-10V 1-10V Dimming	
Colour Temperature	/840 4000k					
Colour	/GR Grey					
Diffuser	/OP Opal			/CL Clear		
Emergency	/ME3 Three hour maintained emergency		/ME3-ST Three hour maintained self test emergency			/ME3-PRO Three hour DALI addressable emergency
To Specify: PYROX LED, with length 748mm, 12W, 1,756lm, 4000k, CRI80, Wire Suspended with an Opal diffuser and Grey finish, completed with standard control gear. Part code: PYROX/12W/1756lm/7/STD/840/GR/OP/WS						

Opal Diffuser Polar Curve



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

- Style
- Range abbreviation
- Wattage
- Lumens
- Size
- Driver
- Colour Temperature
- Options
- Emergency