REVEAL-V2







The REVEAL-V2 is available in two styles and is ideal for pathways, pedestrian zones, courtyards, and small car parks. It features a prismatic or transparent diffuser options, and is compatible with Ø60mm and Ø76mm poles.

- A lumen output of 5400lm or 7800lm
- Colour Temperature: 4000k
- Colours: Black as standard (/BK), other RAL's available
- Standard Non Dimming (/STD)
- Emergency not available
- Mounting: Pole Mounting Ø60 or Ø76mm (/60P/76P)

- IP Rating: IP65
- Distributions: Sysmetrical Area Distribution
- Lens: Clear or Prismatic Difuser (/CL/PD)
- Housing: Die-cast aluminium
- Dimensions of Head: (Diameter x Length x Width)

/CL - Ø610 x 435mm

/PD - Ø600 x 426mm

| Product | MI/REVEAL-V2 IP65 LED Pole Mounted Luminaire | | | |
|---------------------------------------|--|----------------|--------------------------------|----------------|
| Light Source | LED | | | |
| System Power Luminaire lumens (4000K) | /40W 5,400lm | /60W 7800lm | /40W 5300lm | /60W 7800lm |
| Diffuser | /CL Clear | | /PD Prismatic | |
| Size (Diameter x Length x Width) | Ø610 x 435mm | | Ø600 x 426mm | |
| Driver | /STD Non Dimming | | | |
| Distribution | Symetrical | | | |
| Colour Temperature | /740 4000k | | | |
| Mounting | /60P Pole Mounted Via Ø60mm | | /70P Pole Mounted Via Ø70mm | |

To Specify: Reveal V2, 40W, 5400lm, 4000k, Clear Diffuser, pole mounted via Ø60mm pole, finished black, a symmetrical light distribution, and supplied with standard integral control gear.

Part code: MI/REVEAL-V2/CL/40W/5400lm/STD/740/BK/60P

