



SEVENCELL-C a slimline UGR<19 constant-current dark-light linear luminaire with a compact, tool-free design, delivering up to 148 lm/W. Available in 4 or 7 pocket versions, CRI80 standard (CRI90 optional).

- A range of lumen outputs from 751-1800lm
- Colour Temperatures: 2700K - 3000K - 4000K
- Beam Angles: (/35D/50D/80D)
- Colours: Black or White (/BK/WH)
- Available with Dimming (/STD/DALI)
- Wireless Control (/WI)
- Emergency: Not Available
- Reflector Colour: Black or White (/BKR/WHR)
- Diffuser: Opal or Clear (/OP/CL)
- IP Rating: IP20
- CRI80 as standard, CRI90 Available
- Dimensions: (Length x Width x Height)
/7CELL - 295 x 55 x 41mm /4CELL - 155 x 55 x 41mm
- Cut-out Dimensions: (Length x Width)
/7CELL - 285 x 45mm /4CELL - 145 x 45mm

Product	MIR/SEVENCELL-C A Slimline Recessed Linear Luminaire With 7 or 4 Modules					
Light Source	/4CELL			/7CELL		
System Power Luminaire lumens (4000K)	/4.9W 751km	/6W 931lm	/7.5W 111lm	/8.5W 1217lm	/11W 1507lm	/13W 1800lm
Size Cut-out	155 x 55 x 51mm (L x W x H) 145 x 45mm (L x W)			295 x 55 x 51mm (L x W x H) 285 x 45mm (L x W)		
Driver	/STD Non Dimming			/DALI DALI Dimming		
Colour Temperature	/827 2700K		/830 3000K		/840 4000K	
Body Colour	/WH White			/BK Black		
Reflector Colour	/WHR White Reflector			/BKR Black Reflector		
Beam Angle	/35D 35 Degrees		/50D 50 Degrees		/80D 80 Degrees	
To Specify: Slimline recessed linear LED luminaire with 4 modules, constant-current system, 7.5W, delivering 1111lm at 4000K, finished black with black reflector. Supplied with DALI dimming driver, 50° beam angle, complete with remote control gear. Product code: MIR/SEVENCELL-C/4CELL/7.5W/1111LM/840/DALI/BK/BKR/50D						

