



SEVENCELL-V is a slimline UGR<19, 24V dark-light linear luminaire with a compact, plug-and-play design, delivering up to 183 lm/W. With CRI95 as standard, 7 modules, and supports up to 15 fittings from a single 150W remote driver.

- A lumen output of 1500lm
 - Colour Temperatures: 2700K - 3000K - 4000K
 - Beam Angles: (/35D/50D/80D)
 - Colours: Black or White (/BK/WH)
 - Available with Dimming (/STD/DALI)
 - Wireless Control (/WI)
 - Emergency: Not Available
 - Reflector Colour: Black or White
- Diffuser: Opal or Clear (/OP/CL)
 - IP Rating: IP20
 - CRI95 as standard
 - Dimensions: (Length x Width x Height)
295 x 55 x 51mm
 - Cut-out Dimensions: (Length x Width)
285 x 45mm

Product	MIR/SEVENCELL-V A Slimline Recessed Linear Luminaire With 7 Modules		
Light Source	LED		
System Power Luminaire lumens (4000K)	/8W 1500lm		
Size Cutout	295 x 55 x 51mm (LxWxH) 285 x 45mm (L x W)		
Driver	/STD Non Dimming		/DALI 24V DALI Dimming
Colour Temperature	/927 2700K	/930 3000K	/940 4000K
Body Colour	/WH White		/BK Black
Reflector Colour	/WHR White Reflector		/BKR Black Reflector
Beam Angle	/35D 35 Degrees	/50D 50 Degrees	/80D 80 Degrees
To Specify: Slimline recessed linear LED luminaire with 7 modules, 24V system, delivering 1500lm at 4000K, finished in white. Supplied with 24V DALI dimming driver, 50° and complete with remote control gear. Product code: MIR/SEVENCELL-V/8W/1500lm/940/DALI/WH/50D			

