




**- The SITI2, 15W to 200W is an IP66 robust street light,
Suitable for Side Entry or Post Top mounting with adjustable Head Tilt.
A range of light distributions is available. Finished in Matt Black, White or Dark Grey.**

- Providing a lumen output of 2250-30000lm
- Colour Temperature: 3000k, 4000k, 5000k
- Die cast aluminium body
 - Rated IP66 - IK09
- LED sealed within impact resistant clear polycarbonate
- Head Adjustment, -20 to +15 degree adjustment in 5 degree tilt steps.
- Suitable for Side Entry and Post Top. - Will suit 42mm, 60mm and 76mm Spigots

Product	MI/SITI2 Post top IP66 LED Luminaire			
Lamp	LED			
	MICRO	MINI	MADI	MAXI
System Power <small>Luminaire lumens (4000K)</small>	/15W/2250lm /45W/6750lm	/60W/9000lm /90W/13500lm	/90W/13500lm /120W/18000lm	/150W/22500lm /200W/30000lm
Size <small>Length x Width x Depth</small>	448x315x131mm	534x251x132mm	610x285x132mm	630x327x136mm
Driver	/STD Non Dimming			
Colour Temperature	/830 4000k		/840 4000k	/850 5000k
Light Distribution	/TYPE I STANDARD	/TYPE III WIDE ROADS	/TYPE IV CROSSINGS	/TYPE V AREA LIGHTING
Colour	/WH White		/GR Grey, (standard), RAL7037	/BK Black
To Specify: SITI2 LED, 60W, 9000lm, 4000k, LED post top mounted luminaire, TYPE I Distribution, finished Grey supplied complete with standard integral control gear. Part code: MI/SITI2/60W/9000lm/STD/840/TYPE I/GR				



TYPE IV TYPE V
 TYPE I - TYPICAL APPLICATIONS
 TYPE III - WIDE ROADS
 TYPE IV - PEDESTRIAN CROSSINGS
 TYPE V - AREA LIGHTING

