



- An architectural surface and suspended, modular and continuous LED system with an uplight facility.

Uplight/Downlight as standard.

- A range of lumen outputs from 3050-6320lm

- Painted white RAL9016 as standard,
other RAL colours available (/WH)

- Colour Temperatures: 3000k - 4000k - 5000k

- Available with Dimming (/STD/DALI/SDIM)

- Available in Tuneable White (/TWH)

- Uplight/Downlight as standard. Available as downlight only (/DL)

- Catalogue page shows UDL data. DL data available upon request.

- Available with Emergency (/ME3/ME3-ST/ME3-PRO)

- Diffuser Options: Polar White/Micro Prismatic (/PW/MPO)

- Available as surface mounted or wire suspended (/SM/WS)

- Available with wireless control (/WI)

- Dimensions: 1250/1550 x 250 x 76mm

Product	MIS/SPACE2 LED linear luminaire				
Lamp	LED				
Lamp Power Luminaire lumens (4000K)	/21.6W 3050lm	/31.8W 4238lm	/28.9W 4046lm	/44.3W 5848lm	/59.6W 6320lm
Size	/12 1250mm		/15 1550mm		
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming	
Colour Temperature	/830 3000k	/840 4000k	/850 5000k	/TWH Tuneable White	
Colour	/WH White				
Diffuser Options	/PW Polar White Diffuser		/MPO Micro Prismatic Diffuser		
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency	
To Specify: SPACE2 LED, 44.3W, 5848lm, 1550mm, 4000k, LED wire suspended linear finished white supplied complete with DALI control gear, wire suspension, polar white diffuser and direct/indirect distribution. Part code: MIS/SPACE2/LED/44.3W/5848lm/15/DALI/840/WH/PW/WS/UDL					

