




A suspended extruded aluminium luminaire. The SPACE2X is available as a continuous or modular luminaire.
The unique end cap design allows for continuous run integration.

- A lumen outputs of 2555lm or 3308lm
 - Colour Temperatures: 3000k - 4000k
 - Available with Dimming (/STD/DALI/SDIM)
 - Available with Emergency (/ME3/ME3-ST/ME3-PRO)
 - Distribution: Direct or Direct/Indirect options (/DL/UDL)
- Integral control gear for the standard product.
 - Continuous or Modular.
 - Dimensions: (Length x Width x Height)
1486 x 150 x 50mm
Other lengths to suit project requirements

Product	MIS/SPACE2X Suspended Luminaire		
Light Source	LED		
System Power UDL Luminaire lumens (4000K)	/24W 2555lm	/32W 3308lm	
Length	/15 1486mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Colour Temperature	/830 3000k		/840 4000k
Diffuser Options	/PW Polar White		/MPO Micro Prismatic Optic
Distribution Options	/DL Downlight (Direct)		/UDL Uplight & Downlight (Direct/Indirect)
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: SPACE2X, 32W, 4000k, 3308lm LED suspended linear finished white supplied complete with standard control gear, polar white diffuser and Direct/Indirect. Part code: MIS/SPACE2X/32W/3308lm/STD/840/WH/PW/WS/UDL			



MIS/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

Style

Range abbreviation

Wattage

Lumens

Size

Driver

Colour Temperature

Options

Emergency