



- A suspended uplight and downlight SPACE2X. The SPACE2X is continuous up to a four metre length with no joins, past four metres, continuous lengths require joins. The unique end cap design allows for continuous run integration.

- Providing a range of lumen outputs from 2804lm-3697lm
 - Colour Temperatures: 3000k - 4000k
 - Integral control gear for the standard product.
- Product continuous up to 4M length with no joins.
- Continuous lengths past 4M available with joins.
 - Available with Dimming (/STD/DALI/SDIM)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
 - Dimensions: 1500 x 200 x 45mm (L x W x H)

Product	MIS/SPACE2X Suspended Up/Downlight Luminaire		
Lamp	LED		
Lamp Power Luminaire lumens (4000K)	/35.5W 2804lm	/50W 3697lm	
Size	1500 x 200 x 45mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming
Colour Temperature	/830 3000k		/840 4000k
Colour	/WH White		/BK Black
Diffuser Options	/PW Polar White		/MPO Micro Prismatic Optic
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency
To Specify: SPACE2X, 50W, 4000k, 3697lm LED suspended linear finished white supplied complete with standard control gear and polar white diffuser. Part code: MIS/SPACE2X/LED/50W/3697lm/STD/840/WH/PW/WS			

