



- SPACELINE60 range provides an energy efficient and high output LED source in the style of a surface or suspended linear luminaire. With a modern minimalist design the luminaire is suitable for a wide range of applications including offices, meeting rooms, circulation areas and receptions.

- A range of lumen outputs of 1415-3536lm
- A range of standard sizes available from 578mm-3680mm
- Diffuser Options: Polar White / Microprism / Lumieo Panel (/PW/ MPO/MPOLP)
- 5 year system warranty
- Colour Temperatures: 3000k - 4000k
- Available in both downlight and up/downlight options (/DL/UDL)
- Available with Dimming (/STD/DALI/SDIM)
- Available with wire suspension (/WS)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)

Product	MIS/SPL60 Surface LED Linear			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/18.7W 1415lm	/26.1W 2121lm	/33.3W 2829lm	/40.8W 3536lm
Length	/6 578mm	/9 859mm	/12 1139mm	/15 1420mm
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming
Colour Temperature	/830 3000k	/840 4000k		/TWH Tunable White
Colour	/WH White			
Diffuser Options	/PW Polar White	/MPO Micro Prismatic Optic		/MPOLP MPO with Lumieo
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency
To Specify: SPACELINE60 LED, 33.3W, 4000k, 2829lm, 1139mm, LED modular suspended downlight finished white supplied complete with DALI control gear and polar white diffuser. Part code: MIS/SPACELINE60/LED/33.3W/2829lm/12/DALI/840/DL/WH/PW/WS				

