



A range of high efficiency, low maintenance, reliable luminaires for exterior applications. Sealed to IP68 and suitable for exterior, garden applications specifically tree and facade lighting.

- A range of lumen outputs from 140-1100lm
- Colour Temperature: 3000k - 4000k
- Beam Angle: 15°, 40° or 60° (/15D/40D/60D)
- Lens: 8mm Tempered glass lens
- Colour: Stainless steel bezel as standard
- Supplied complete with remote LED driver
- Emergency options not available
- Mountings: stake mount - optional (/STK)
- IP Rating: IP68
- CRI80 as standard, CRI90 available
- Glass Options: Clear Glass or Frosted Glass (/CL/FG)
- Recessing box available
- Anodized aluminium
- Contact technical for further information on recessing box
- Dimensions: See table below

Product	MI/SUPA Exterior IP68 LED Luminaire		
Light Source	LED		
System Power Luminaire lumens (4000K)	/2W 140lm	/4.8W 420lm	/11W 1100lm
Size	Ø40 x 65mm	Ø68 x 54mm	Ø68 x 100mm
Driver	/STD Non Dimming		
Colour Temperature	/830 3000k		/840 4000k
Glass Options	/CL Clear Glass		/FG Frosted Glass
Beam Options	/15D 15 Degree	/40D 40 Degree	/60D 60 Degree
To Specify: SUPASPOT LED, 11W, 1100lm, 4000k, LED surface mounted finished anodized aluminium complete with remote control gear, clear glass and a 60 degree beam angle. Part code: v			

Dimensions 4.8W Version

