



The TRK-1 is a track luminaire with a sleek, minimalistic design, ideally suited for retail, hospitality and leisure environments. Compatible with Global Trac® systems. Visit www.midlighting.co.uk for full track details.

- A lumen outputs of 690lm or 2000lm
 - Colour Temperatures: 2700k - 3000k- 4000k
 - Beam Angles : 12°, 15°, 25°, 35°, 45° or 60°
(/12D/15D/25D/35D/45D/60D)
 - Colours: White or Black (/WH/BK)
 - Available with Dimming (/STD/DALI)
 - Wireless Control (/WI)
 - Honey Comb Attachment available (/HC)
- Refer to track system page 84 for the following mountings, Surface, Recessed and Wire suspended
 - TRK-1 head rotates 355 degrees and pivots through 90 degrees. The rotating position can be set by the scale marked on the connection to the body.
 - CRI90 as standard
 - Dimensions: (Diameter x Height)
Ø50mm x 124mm

Product	MI/TRK-1 LED TRK Spotlight					
Light Source	LED					
System Power Luminaire lumens (4000K)	/7W 690lm	/10W 1250lm	/11.5W 1500lm		/15.5W 2000lm	
Beam Angle	12D 12 Degrees	/15D 15 Degrees	/25D 25 Degrees	/35D 35 Degrees	/45D 45 Degrees	/60D 60 Degrees
Driver	/STD Non Dimming		/DALI DALI Dimming		/WI Wireless Control	
Colour Temperature	/927 2700k		/930 3000k		/940 4000k	
Colour	/WH White			/BK Black		
Size Diameter x Height	Ø50mm x 124mm					
Emergency	Remote EMLED TRK available. See Page 263 for details.					
To Specify: TRK-1, 15.5W, 4000k, 2000lm, 35 degrees beam angle, LED track spotlight supplied with DALI control gear and finished in black. Part code: MI/TRK-1/15.5W/2000lm/DALI/840/35D/BK						

