



The TRK-3 is a track luminaire that is suitable for single of three circuit Global Trac® systems. Ideal for retail, hospitality and leisure applications.

- A range of lumen outputs from 1352-4088lm
- Colour Temperatures: 3000k - 4000k
- Beam Angles: 26°, 38° or 60° (/26D/38D/60D)
- Colours: White RA9016 or Black RA9005 (/WH/BK)
- Available with Dimming (/STD/DALI)
- Refer to track system page 84 for the following mountings, Recessed and Wire suspended
- Available with surface mounting adapter (/SMA)
- TRK-3 head rotates and pivots to allow adjustable aiming of luminaire.
- Compatible with Global Trac® Systems.
- Dimensions: (Diameter x Height)
Ø100 x 218mm

Product	MI/TRK-3 LED TRK Spotlight			
Light Source	LED			
System Power Luminaire lumens (4000K)	/11.5W 1352lm	/18.3W 2117lm	/26.6W 2846lm	/38.2W 4088lm
Size	Ø100 x 218mm			
Driver	/STD Non Dimming		/DALI DALI Dimming	
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White RAL9016		/BK Black RAL9005	
Beam Angle	/26D 26 Degrees	/38D 38 Degrees		/60D 60 Degrees
Emergency	Remote EMLED TRK available. See Page 263 for details.			
To Specify: TRK-3, 18.3W, 4000k, 2117lm, 60 degree beam angle, LED track spotlight supplied with DALI control gear and finished in black. Part code: MI/TRK-3/18.3W/2117lm/DALI/840/BK/60D				

Side And Front Profile View Dimensions

