





The TRK-4 is a track luminaire with a sleek, minimalistic design, ideally suited for retail, hospitality and leisure environments. The TRK-4 is a driver inside track unit.

- A range of lumen outputs from 1300lm or 1700lm
- Colour Temperatures: 3000k 4000k
- Beam Angles: 15°, 25° or 30° (15D/25D/30D)
- Colours: White or Black (/WH/BK)
- Available with Dimming (/STD/DALI)
- Refer to track system page 84 for the following mountings, Recessed and Wire suspended
- -TRK-4 head rotates 355 degrees and pivots through 90 degrees. The rotating position can be set by the scale marked on the connection to the body
- CRI80 as standard, CRI90 Available
- Dimensions: (Diameter x Height)

Ø72 x 138mm

| Product | MI/TRK-4 LED TRK Spotlight | | | |
|--|---|----------------------|-----------------------|----------------------|
| Light Source | LED | | | |
| System Power Luminaire lumens (4000K) | /15W 1300lm | | /21W 1700lm | |
| Size | Ø72 x 138mm | | | |
| Driver | /STD Non Dimming | | /DALI DALI Dimming | |
| Colour Temperature | /830 3000k | /930 CRI 90 3000k | /840 4000k | /940 CRI 90 4000k |
| Colour | /WH White | | /BK Black | |
| Beam Angle | /15D 15 Degrees | /25D 25 Degrees | | /30D 30 Degrees |
| Emergency | Remote EMLED TRK available. See Page 263 for details. | | | |

To Specify: TRK-4, 21W, 4000k, 1700lm, 30 degree beam angle, LED track spotlight supplied with DALI control gear and finished in black. Part code: MI/TRK-4/21W/1700lm/DALI/840/30D/BK

