



The Cell range includes 4-cell and 7-cell linear fittings, available for track, surface, or recessed mounting. Its compact and distinctive design delivers both versatility and a sleek, contemporary aesthetic.

- A range of lumen outputs from 897-1436m
- Colour Temperatures: 3000k - 4000k
- Beam Angles: (/50D/80D)
- Colours: Black or White (/BK/WH)
- Available with Dimming (/STD/DALI)
- Refer to track system page **84** for the following mountings, Recessed and Wire suspended
- CRI80 as standard, CRI90 available
- Dimensions: (Length x Width x Height)
285 x 50 x 85mm

Product	MI/TRK-7CELL LED Linear Lamp Suited For Track			
Light Source	LED			
System Power Luminaire lumens (4000K)	/6W 897lm	/7.1W 1077m	/8.2W 1256m	/9.4W 1436lm
Size	285 x 50 x 85mm (Length x Width x Height)			
Driver	/STD Non Dimming		/DALI DALI Dimming	
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White RAL9016		/BK Black RAL9005	
Beam Angle	/50D 50 Degrees		/80D 50 Degrees	
Emergency	N/A			
To Specify: MID/7CELL 8.2W, 4000k, 1256lm, 50 degree beam angle, LED surface mounted linear spotlight supplied with DALI control gear and finished in black. Part code: MID/4CELL/8.3W/1256lm/DALI/840/BK/50D				

Recessed Verisoon
MIR/4CELL



Surface Mounted
Verisoon MIS/4CELL

