



TUBE/125



TUBE/150



TUBE/200

**THE Tube SLIM is a surface or suspended minimalist cylindrical downlight with a durable aluminium build.**

**The suspended model offers adjustable drop height, ideal for adding visual interest in architectural settings.**

- A range of lumen outputs 1881-3244lm
- Colour Temperatures: 3000K - 4000K
- Colours: White or Black (/WH/BK)
- Available with Dimming (/STD/DALI)
- Wireless Control (/WI) & Wireless Emergency (/ME3-WI)
- Emergency: (/ME3/ME3-ST/ME3-PRO)
- Mounting: Surface mounted or Wire suspended (/SM/WS)
- Beam Angles: (/10D/20D/30D/45D/50D)
- IP Rating: IP20
- Dimensions: (Diameter x Depth)  
 Ø125 x 170mm  
 Ø150 x 250mm  
 Ø200 x 220mm

LED Products	TUBE								
Diameter	/125 Ø125mm			/150 Ø152mm			/200 Ø200mm		
System Power Luminaire lumens (4000K)	/14.4W 1881lm	/16.1W 2116lm	/17.9W 2351lm	/14.4W 1881lm	/16.1W 2116lm	/17.9W 2351lm	/16.1W 2116lm	/20W 2974lm	/21.8W 3244lm
Beam Angle	/20D 20° Beam	/30D 30° Beam	/50D 50° Beam	/20D 20° Beam	/30D 30° Beam	/50D 50° Beam	/10D 10° Beam	/30D 30° Beam	/45D 45° Beam
Driver	/STD Non Dimming			/DALI DALI Dimming			/WI Wireless Control		
Colour Temperature	/830 3000k					/840 4000k			
Colour	/WH White					/BK Black			
Emergency	/ME3 Three hour maintained emergency		/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency		/ME3-WI Three hour Wireless addressable emergency		
To Specify: TUBE with a Ø125mm, 14.4W, 4000K, 1881lm LED surface can, finished white, surface mounted, supplied with a 20° beam reflector and standard non-dimming driver. Part code: TUBE/125/14.4W/1881lm/STD/840/WH/20D/SM									

Black Version  
TUBE-SLIM/125

