

# TUBE BAY



**The IP66 Tube Bay luminaire is a linear Hi-bay suitable for food processing, warehouses and cold environments.**

- A range of lumen outputs from 7,500-20,000lm
- Colour Temperatures: 4000k - 5000k
- Beam Angles: 120° (/120D)
- Available with Dimming (/STD/1-10V)
- Shatter proof polycarbonate Lens
- Mountings: Surface mounted, Wall mounted or Wire suspended (/SM/WM/WS)
- Diffuser: Opal
- IP Rating: IP66
- IK Rating: IK10
- Die cast aluminium alloy housing and a heat dissipating powder coat finish
- Dimensions: (Length x Diameter)
  - /12 - 1255 x Ø80mm
  - /24 - 2474 x Ø80mm
- Height of cap: 113mm

Product	MI-TBAY Industrial LED Luminaire			
Light Source	LED			
System Power	/58W 7,500lm	/80W 10,000lm	/80W 10,000lm	/160W 20,000lm
Size (LxWxH)	/12 1255 x Ø80mm		/24 2474 x Ø80mm	
Driver	/STD Non Dimming		/1-10V 1-10V Dimming	
Colour Temperature	/840 4000k		/850 5000k	
Diffuser	Opal			
Mountings	/SM Surface mounted	/WM Wall mounted	/WS Wire suspended	
Emergency	n/a			
To Specify: MI-TBAY LED, 58W, 7500lm, 4000k, size 1255mm, opal diffuser and surface mounted with standard control gear. Part code: MI-TBAY/58W/12/7500lm/STD/840/OP/SM				

