

V-ILS ENGINES



The V-ILS engines are highly efficient with its compact design and a wide range of bezels to tailor to your desired finish.

- A lumen output of 950lm or 1429lm
- Colour Temperatures: 2700k - 3000k - 4000k
- Beam Lens: 15°, 25°, 35° or 60° (/15D/25D/35D/60D)
- Available with Dimming (/STD/1-10V/DALI/MDIM)
- Wireless Control available (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/ME3-WI)
- Reflectors Colours: Black or Gold (/BKR/GDR)
- IP Rating: IP44
- CRI80 as standard, CRI90 Available
- Made from aluminium and electroplating
- Dimensions: (Diameter x Height x Width)
Ø50 x 65 x 63mm
- Honey comb attachment available (/HC)

Product	V-ILS V-ILS Engine				
Light Source	LED				
System Power Luminaire lumens (4000k)	/10.6W 1016lm		/14.8W 1429lm		
Size	Ø50 x 65 x 63mm				
Driver	/STD Non Dimming	/1-10V 1-10V Dimming	/DALI DALI Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/827 2700K		/830 300K		/840 400K
Reflector Colours	/BKR Black Reflector			/GDR Gold Reflector	
Beam Angle	/15D 15 Degrees	/25D 25 Degrees	/35D 35 Degrees	/60D 60 Degrees	
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three DALI addressable emergency	/RME3-WI Remote three hour wireless addressable emergency	
To Specify: V-ILS, D5, 10.6W, 1016lm, 4000k, LED downlight with 15 degree narrow beam lens and DALI control gear, finished with a gold reflector. Part code: MID/V-ILS/D5/10.6W/1016lm/DALI/840/15D/GDR					

