



- **An architectural, circular, IP65, ultra shallow LED solution.**

- **Semi-Recessed; ideal for restricted voids**

- Available in 8W (Ø 100mm), 11W (Ø 125mm), 15W (Ø 155mm), 22W (Ø 185mm) & 30W (Ø 215mm)
 - Circular: 569/856/1178/1749/2230 lumens
- Shallow Depth: 20mm (depth without driver, driver depth may vary)
 - Available with Dimming (/STD/DALI/SDIM/MDIM)
 - Colour Temperatures: 3000k - 4000k - 6500k
 - Bezel Options: White (/WH)
- Available with remote Emergency (/RME3/RME3-ST/RME3-PRO)

Product	MIR/WAF-P/C Semi-Recessed WAFER-P Circular					
Lamp	LED					
Lamp Power <small>Luminaire lumens (4000K)</small>	/8W 569lm	/11W 856lm	/15W 1178lm	/22W 1749lm	/30W 2230lm	
Size <small>Cut-out</small>	Ø 100mm Ø 80mm	Ø 125mm Ø 105mm	Ø 155mm Ø 135mm	Ø 185mm Ø 165mm	Ø 215mm Ø 195mm	
Driver	/STD Non Dimming	/DALI DALI Dimming		/SDIM Switch Dimming	/MDIM Mains Dimming	
Colour Temperature	/830 3000k	/840 4000k			/865 6500k	
Bezel Colour	/WH White					
Diffuser Options	/OP Opal Diffuser					
Emergency	/RME3 Remote Three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency			/RME3-PRO Remote Three hour DALI addressable emergency	
To Specify: WAFER-P CIRCULAR LED, 15W, 4000k, 1178lm LED semi-recessed downlight finished white supplied complete with remote control gear. Part code: MIR/WAF-P/C/15W/1178lm/STD/840/WH/OP						

